

## Ultronic™ Plus and Premium Hand Dryers

### Technical specifications

Hand Dryer Model	Ultronic™ -1 Plus	Ultronic™ -1 Premium	Ultronic™ -2 Plus	Ultronic™ -2 Premium
<b>Item number</b>	205634	205636	205635	205637
<b>ELECTRICAL DATA</b>				
<b>Phase - 60/50 Hz</b>	single	single	single	single
<b>Voltage</b>	120 V	120 V	240 V or 208 V	240 V or 208 V
<b>Wattage</b>	820 W	820 W	750 W      640 W	750 W      640 W
<b>Amperage</b>	6.8 A	6.8 A	3.5 A      3.5 A	3.5 A      3.5 A
<b>Required circuit breaker size<sup>1</sup></b>	15 A	15 A	15 A	15 A
<b>Required wire size<sup>2</sup></b>	16 AWG	16 AWG	18 AWG	18 AWG
<b>DIMENSIONS</b>				
<b>Height</b>	12 <sup>3</sup> / <sub>16</sub> " (309 mm)	12 <sup>3</sup> / <sub>16</sub> " (309 mm)	12 <sup>3</sup> / <sub>16</sub> " (309 mm)	12 <sup>3</sup> / <sub>16</sub> " (309 mm)
<b>Width</b>	10 <sup>11</sup> / <sub>16</sub> " (272 mm)	10 <sup>11</sup> / <sub>16</sub> " (272 mm)	10 <sup>11</sup> / <sub>16</sub> " (272 mm)	10 <sup>11</sup> / <sub>16</sub> " (272 mm)
<b>Depth</b>	5 <sup>3</sup> / <sub>16</sub> " (132 mm)	5 <sup>3</sup> / <sub>16</sub> " (132 mm)	5 <sup>3</sup> / <sub>16</sub> " (132 mm)	5 <sup>3</sup> / <sub>16</sub> " (132 mm)
<b>Weight</b>	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)
<b>CONSTRUCTION</b>				
<b>Color</b>	Alpine White	Stainless Steel	Alpine White	Stainless Steel
<b>Housing</b>	Polycarbonate	Stainless Steel	Polycarbonate	Stainless Steel
<b>Degree of protection (IP)</b>	IP X3			
<b>OTHER</b>				
<b>Sound pressure level</b>	76 dB(A) @ 1m (68 dB(A) @ 1m in quiet-mode)			
<b>Air speed</b>	215 mph (96 m/s)			
<b>Air volume</b>	49.5 CFM			
<b>Drying time</b>	10-12 seconds			

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary. <sup>2</sup> Copper must be used



Conforms to UL Std. 50  
Certified to CAN/CSA C22.2 No. 113

