

**STIEBEL ELTRON**

Simply the Best

Elegant, stylish warmth



## Electric Space Heaters

FAN | CONVECTION

- › Quiet & attractive space heating
- › Easy, surface-mount installation
- › Safe, efficient, clean heat
- › Supplemental or primary heating options



ISO 9001  
CERTIFIED

800.582.8423

[www.stiebel-eltron-usa.com](http://www.stiebel-eltron-usa.com)

## Ways to heat

Stiebel Eltron CK and CKT wall-mounted fan heaters use a small, quiet fan to pull in room air and send out heated air. These heaters are perfect for spaces like bathrooms that already have a primary heat source, but may need a little extra heat added quickly. They can also be used as the primary heat source in a small room or space, such as a hallway or small bedroom.

Our CNS-E wall-mounted convection heaters have no fan. Using the natural process of convection, air heated inside a

CNS-E heater naturally rises out the top as cooler air is pulled into the bottom to be heated. A single CNS-E heater can provide heat for smaller spaces like bathrooms, bedrooms, and hallways. Multiple CNS-E heaters can easily be used to heat a larger space. CNS-E heaters have an integral thermostat but can be linked to a central thermostat. They make an excellent replacement for baseboard heating.



## Where are you looking to warm up?

We have several options for whatever space you need to make cozy. Warming up just a bathroom, hallway, or bedroom or do you need a primary heat source for a large living room? Tired of looking at electric baseboard heaters and want a stylish, energy efficient replacement? Do you need to spot heat a workshop or work station, or an outdoor eating or seating area? The tables on the back page will help you choose the best heater for your needs.

# STIEBEL ELTRON

# Electric Space Heaters

## CK Series | Quiet Fan Heaters

The CK, CKT, and CK Trend are designed and made in Germany. These elegant, surface-mount fan heaters are extremely quiet.

They are a simple solution to quickly add heat to a room that may not get enough heat from a central source, as sometimes happens with a mini-split retrofit, or they can add heat to a space that never had it before, like a porch retrofit.

CK, CKT, and CK Trend heaters have an integral thermostat, but the CK can be linked to a central thermostat if it is installed in a room larger than 215 sq. ft.

Need to occasionally warm a room more than the thermostat is set for? The CKT, the boost timer version of the CK, is designed to add additional heat to a space when desired. Set the timer on the CKT for up to 60 minutes and the CKT outputs heat at its maximum setting. When the timer goes off, the CKT reverts to its thermostat setting, maintaining comfort at the original setting.

All CK Series models are designed with a frost protection setting. The lowest thermostat setting will maintain above freezing temperatures in an appropriately sized space.

- › Extremely quiet operation
- › Built-in thermostat
- › Convenient 60-minute boost timer on CKT
- › Downdraft design for even heat



## CK Series



Certified to ANSI/UL Std. 2021  
Conforms to CAN/CSA Std. 22.2 No. 46



Complete warranty online.



Model	CK 15 E	CKT 15 E	CK 150-1 Trend	CK 200-2 Trend
Item number	074058	230345	236304	236305
Voltage	120 V	120 V	120 V	240 V or 208 V
Wattage	1500 W	1500 W	1500 W	2000 W   1800 W
Amperage	12.5 A	12.5 A	12.5 A	8.3 A   8.7 A
Rated output Btu/hr	5118	5118	5118	6824   6142
Air volume	106 CFM	106 CFM	70.6 CFM	70.6 CFM
Recommended circuit breaker size <sup>1</sup>	15 A	15 A	15 A	15 A
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG	14 AWG
Timer	no	yes	N/A	N/A
Room size estimate	150 sq.ft.	150 sq.ft.	150 sq.ft.	200 sq.ft.
Heating element	nichrome wire		ceramic positive temperature coefficient (PTC)	
Thermostat & high limit	bimetal type		bimetal type	
Motor	18 W shaded pole		20 W shaded pole	
Blower	galvanized steel, squirrel cage type		glass-reinforced polycarbonate, radial type	
Dimensions	H 18 1/8" (460 mm) x W 13 3/16" (335 mm) x D 4 3/16" (123 mm)		H 15 3/4" (400 mm) x W 10 7/8" (275 mm) x D 5 1/8" (131 mm)	
Weight	8.0 lb (4.4 kg)		5.5 lb (2.5 kg)	
Temperature range	41-86 °F (5-30 °C)		45-95 °F (7-35 °C)	
Frost protection setting	45 °F (7 °C)		45 °F (7 °C)	
Operating noise	49.7 dB(a)		49.0 dB(a)	

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary.

- › Attractive slimline european design
- › Thermostat built into unit
- › Baseboard heater alternative
- › Draft-free, silent operation

## CNS Series | Silent Convection Heaters

The CNS-E is a modern surface-mounted convection heater with a sleek European slimline design. CNS-E units are an effective, efficient replacement for traditional baseboard heaters, using significantly less room to accomplish the same heating task.

CNS-E heaters work through natural convection, ensuring draft-free operation. Cool room air flows in the bottom of the unit, is warmed by the heating element, and rises silently out the top to heat the room. The CNS-E is designed with a frost protection setting. The lowest thermostat setting will maintain an appropriately-sized room above freezing temperatures.

With its built-in thermostat, a single CNS-E is perfect as a stand-alone heating system in bathrooms or small rooms. Multiple CNS-E units can be placed strategically in larger spaces and their temperature settings adjusted individually for maximum comfort control. If used to replace an existing heater with a separate wall-mounted thermostat control, CNS-E heaters may be wired to use that control. Overheat protection is built into the unit.

## CNS Series



Certified to ANSI/UL Std. 2021  
Conforms to CAN/CSA Std. 22.2 No. 46



Complete warranty online.



Model	CNS 100-1 E	CNS 150-1 E	CNS 100-2 E		CNS 150-2 E		CNS 200-2 E		CNS 240-2 E	
Item number	233586	233587	231543		231544		231545		231546	
Voltage	120 v	120 v	240 v or 208 v		240 v or 208 v		240 v or 208 v		240 v or 208 v	
Wattage	1000 w	1500 w	1000 w	750 w	1500 w	1125 w	2000 w	1500 w	2400 w	1800 w
Amperage	8.3 A	12.5 A	4.2 A	3.6 A	6.3 A	5.4 A	8.3 A	7.2 A	10.0 A	8.7 A
Btu/hr	3412	5118	3412	2559	5118	3839	6824	5118	8189	6142
Required circuit breaker size <sup>1</sup>	15 A	15 A	15 A		15 A		15 A		15 A	
Required wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG		14 AWG		14 AWG	
Temperature range	45 °F–86 °F (7 °C–30 °C)									
Frost protection setting	45 °F (7 °C)									
Height	17 3/4" (45.0 cm)									
Width	17 1/2" (44.5 cm)	23 1/4" (59.0 cm)	17 1/2" (44.5 cm)	23 1/4" (59.0 cm)	29 1/8" (74.0 cm)	35 1/16" (89.0 cm)				
Depth	3 15/16" (10 cm)									
Weight	9.7 lb (4.4 kg)	12.6 lb (5.7 kg)	9.7 lb (4.4 kg)	12.6 lb (5.7 kg)	15.0 lb (6.8 kg)	17.9 lb (8.1 kg)				
Equivalent Baseboard <sup>2</sup>	4'	6'	4'	6'	8'	9.6'				
Room size estimate <sup>3</sup>	100 sq.ft	150 sq.ft.	100 sq.ft.	150 sq.ft.	200 sq.ft.	240 sq.ft.				

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary.

<sup>2</sup> For comparison purposes only. Exact equivalent will depend on your climate. <sup>3</sup> Based on average insulation

## What do you need to do?

	CK Fan Heater	CKT Fan Heater	CK Trend Fan Heater	CNS-E Convection Heater
Provide primary heat to a space	✓	✓	✓	✓
Provide supplemental heat to a room that already has heat?	✓	✓	✓	✓
Find a replacement for baseboard heating?				✓
Find the quickest way to heat a space?	✓	✓	✓	
Draft-free heating?				✓
Boost heat temporarily though a timer (like in a bathroom in the morning)?		✓		
Heat people or objects in an area without heating the whole space?				
Heat a patio or deck?				

## Features

	CK Fan Heater	CKT Fan Heater	CK Trend Fan Heater	CNS-E Convection Heater
Timer boost function		✓		
Frost protection setting (45°F / 7°C)	✓	✓	✓	✓
Can be controlled by central thermostat	✓			✓
Operating noise	49.7 dB(a)	49.7 dB(a)	49 dB(a)	Silent
Thermostat temperature range	41-86°F (5-30°C)	41-86°F (5-30°C)	45-95°F (7-35°C)	41-86°F (5-30°C)
Can be installed outdoors				

## Stiebel Eltron Energy-Saving Water Heating Products



Efficient electric tankless water heaters

Tankless Water Heating



Point-of-use Tankless      Whole House Tankless

Renewables



Solar hot water      Heat Pump Water Heaters



Low carbon, renewable energy domestic hot water systems

Distributed by:



Stiebel Eltron's plant in Holzminden, Germany.

Stiebel Eltron has been a world leader in the development of advanced water heating technology for more than 90 years. Our pursuit of engineering excellence and high-quality manufacturing results in products fulfilling the highest expectations of performance and reliability. They are...**Simply the Best.**

# STIEBEL ELTRON

17 West Street  
West Hatfield, MA 01088

TOLL FREE 800.582.8423

PHONE 413.247.3380

FAX 413.247.3369

info@stiebel-eltron-usa.com

www.stiebel-eltron-usa.com

Due to our continuous process of engineering and technological advancement, specifications may change without notice.

Printed on recycled chlorine-free paper with soy-based inks. \*14f-8.2019