

Simply the Best

2018.3 MSRP FOR PLUMBING WHOLESALERS Effective August 1, 2018

MSRP

POINT-OF-USE TANKLESS ELECTRIC WATER HEATERS

Electro-mechanical models.

Mini [™] S	Mini [™] Series '199.00				
231045	Mini™ 2-1	120 v, 1.8 kw, single phase	Restricted to 0.32 gpm. Ships with 0.5 gpm aerator		
232098	Mini™ 2.5-1	120 V, 2.4 kW, single phase	Ships with 0.5 gpm aerator		
220816	Mini™ 3-1	120 v, 3.0 kw, single phase	Ships with 0.5 gpm aerator		
232099	Mini™ 3.5-1	120 v, 3.5 kw, single phase	Ships with 0.66 gpm aerator		
222039	Mini™ 4-2	240 v 3.5 kw / 208 v 2.6 kw, single phase	Ships with 0.66 gpm aerator		
220817	Mini [™] 6-2	240 v 5.7 kw / 208 v 4.3 kw, single phase	Ships with 1.0 gpm aerator		



Thermostatic models, electronically controlled. For one or two taps.

Adding a Stiebel Eltron TLC Assembly to a Mini"-E will meet the requirements of UPC 413.1/ASSE 1070. See TLC assemblies in Tankless Accessories.

Mini [™] -E Series			Factory Set Temperature \$299.00	
			Custom Set Temperature	
			\$329.00	
236011	Mini [™] -E 2-1	120 V, 1.8 kW, single phase	Restricted to 0.40 gpm.	
			Ships with 0.5 gpm aerator	
236135 [*]	Mini™-E 2.5-1	120 v, 2.4 kw, single phase	Ships with 0.5 gpm aerator	
236010	Mini™-E 3-1	120 v, 3.0 kw, single phase	Ships with 0.5 gpm aerator	
236136 [*]	Mini™-E 3.5-1	120 v, 3.5 kW, single phase	Ships with 0.5 gpm aerator	
236009	Mini™-E 4-2	240 v 3.5 kw / 208 v 2.6 kw, single phase	Ships with 0.5 gpm aerator	
236008	Mini™-E 6-2	240 v 5.7 kw / 208 v 4.3 kw, single phase	Ships with (2) 0.5 gpm aerators	



Mini[™]-E models are factory set for 100°F output.

Custom settings are available at 95, 96, 98, 101, 102, 103, 104, 105, 106, 108 °F (within the heating limits of the model). Order custom set by specifying "XXXXXX-__F" when ordering. (Part number followed by temperature in Farenheit.)

POINT-OF-USE TANKLESS ELECTRIC WATER HEATERS

Electro-mechanical models.

DHC Series			⁵ 229.00	
074050	DHC 3-1	120 V 3.0 kW, single phase	*	
074052	DHC 3-2	240 V 3.3 kW / 208 V 2.5 kW, single phase	*	
074053	DHC 4-2	240 V 3.8 kW / 208 V 2.9 kW, single phase	*	
074051	DHC 4-3	277 V 4.5 kW, single phase		
074054	DHC 5-2	240 V 4.8 kW / 208 V 3.6 kW, single phase		
074424	DHC 6-2	240 v 6.0 kW/ 208 v 4.5 kW, single phase		
074055	DHC 8-2	240 v 7.2 kW/ 208 v 5.4 kW, single phase		
232204	DHC 9-3	277 v 9.0 kw, single phase		
074056	DHC 10-2	240 V 9.6 kW / 208 V 7.2 kW, single phase		



WHOLE HOUSE OR MULTIPLE TAPS TANKLESS ELECTRIC WATER HEATERS

Thermostatic models, electronically controlled.

Adding a Stiebel Eltron TLC Assembly to a DHC-E will meet the requirements of UPC 413.1/ASSE 1070. See TLC assemblies in Tankless Accessories.

DHC-E			
224201	DHC-E 8/10	240 v 7.2 kw / 208 v 5.4 kw, single phase	\$319.00
		240 v 9.6 kw / 208 v 7.2 kw, single phase	
		two models in one! able to 7.2 kW or 9.6 kW during installation.	
230628	DHC-E 12	240 v / 208 v 12.0 kw, single phase	\$339.00



TANKLESS ELECTRIC GAS OR ELECTRIC TANK BOOSTER

Electronically controlled.

MegaBoost			
524201	MegaBoost	240 v 9.6 kW / 208 v 7.2 kW, single phase	\$389.00




^{*}Ships with 0.5 gpm aerator

WHOLE HOUSE OR MULTIPLE TAPS TANKLESS ELECTRIC WATER HEATERS


Electronically controlled.

Tempra® white models replace the gray models, and have additional features. The Tempra® Trend replaces the Tempra® B and has a digital display for accurate temperature delivery and maximum energy efficiency. The Tempra® Plus replaces the same named previous model. It has an enhanced digital display with monitors for cost savings and water flow, and two preset temperature memory keys. The Tempra® Plus continues to have Stiebel Eltron's German-patented industry-exclusive, Advanced Flow Control®.

Tempra	@		
239213	Tempra® 12 Trend	208, 220-240 V, 12.0 kW, single phase	\$564.00
239219	Tempra® 12 Plus	208, 220-240 V, 12.0 kW, single phase	§679.00
239214	Tempra® 15 Trend	208, 220-240 V, 14.4 kW, single phase	^{\$} 744.00
239220	Tempra® 15 Plus	208, 220-240 V, 14.4 kW, single phase	\$879.00
239215	Tempra® 20 Trend	208, 220-240 V, 19.2 kW, single phase	⁵ 784.00
239221	Tempra® 20 Plus	208, 220-240 V, 19.2 kW, single phase	\$919.00
239216	Tempra® 24 Trend	208, 220-240 V, 24.0 kW, single phase	\$824.00
239222	Tempra® 24 Plus	208, 220-240 V, 24.0 kW, single phase	\$959.00
239217	Tempra® 29 Trend	208, 220-240 V, 28.8 kW, single phase	\$864.00
239223	Tempra® 29 Plus	208, 220-240 V, 28.8 kW, single phase	\$999.00
239218	Tempra® 36 Trend	208, 220-240 V, 36.0 kW, single phase	\$924.00
239225	Tempra® 36 Plus	208, 220-240 V, 36.0 kW, single phase	\$1059.00
	ETL / C-ETL listed for U	SA / Canada. Made in Germany.	



Tempra® Plus Series 12 - 36 kW



Tempra® Trend Series 12 - 36 kW


Tempra® models wired to 208 V single phase will output 75% of the 240 V rating. Tempra® 29 & 36 models may be wired for balanced 3-phase 208 V.

Tempra® 15, 20, 24 models may be wired for unbalanced 3-phase 208 v.

POINT-OF-USE MINI-TANK WATER HEATERS

With T&P valve, cord with plug.


SHC Mini-tank			
233219	SHC 2.5	2.5 gal., 120 v, 1.3 kW, single phase	⁵ 219.00
234046	SHC 4	4 gal., 120 v, 1.3 kW, single phase	§269.00
235089	SHC 6	6 gal., 120 v, 1.3 kw, single phase	§319.00



HEAT PUMP WATER HEATERS


True heat pump water heater.

233058	Accelera® 220 E 240 V	⁵ 2,999.00
	58 gal., 2.15 kW max power input	
233059	Accelera® 300 E 240 v	§3,199.00
	80 gal., 2.15 kW max power input	



WALL-MOUNTED TANK WATER HEATERS

235968	PSH 20 Plus	⁵ 569.00
	21 gal., 240 v, 3.0 kW, single phase	
328651	PSH Plus Drain Pan	\$ 69.0 0
	wall-mounted	



DOMESTIC HOT WATER STORAGE TANKS


For solar thermal, geothermal, or indirectly-fired applications.


224110	SB 300 E	\$2099.00
	79 gal., single coil, integral resistance element	
234111	SB 400 E	\$2499.00
	106 gal., single coil, integral resistance element	
221222	SBB 400 S	°2199.00
	109 gal., single coil	
187873	SBB 300 Plus	\$2299.00
	81 gal., dual coil	
187874	SBB 400 Plus	\$2499.00
	109 gal., dual coil	
187875	SBB 600 Plus	⁵ 2699.00
	163 gal., dual coil	



TANKLESS ACCESSORIES

502346	Mini [™] -E TLC Assembly	⁵ 290.00
	UPC 413.1 compliant temperature limiting control for Mini™-E, completely assembled, includes ASSE 1070 mixing valve	
581012	DHC-E TLC Assembly	\$290.00
	UPC 413.1 compliant temperature limiting control for DHC-E, conmpletely assembled, includes ASSE 1070 mixing valve	
550457	ASSE 1070 Mixing Valve for Mini™-E	\$99.00
	3/8" comp. mixing valve alone for Mini*-E	
550455	ASSE 1070 Mixing Valve for DHC-E	\$99.00
	1/2" mixing valve alone for DHC-E	
540444	Lead-free Brass Isolation Valve Kit	\$139.00
	Cold inlet & hot outlet isolation valves, pressure relief valve	
540000	Flow-aide Tankless Descaling Kit	\$275.00
	3.5 Gal. bucket, 350 GPH pump, 2 5' rubber hoses, 1 qt. fluid	
540002	Flow-aide Fluid Refill	\$39.00
	1 quart	
692442	Scale TAC-ler	\$489.00
	6 GPM water conditioner for scale prevention, includes 1 cartridge	
692443	Replacement Scale TAC-ler Cartridge	⁵ 289.00
	Cartridges have approximate 2-year life	











5

ELECTRIC SPACE HEATERS


Surface mounted.

CK Tren	d fan heater		\$1 49.00
236304	CK 150-1 Trend	120 V, 1.5 kW, single phase	
236305	CK 200-2 Trend	240 V / 208 V, 2.0 kW. single phase	
CK fan	heater		\$185.00
074058	CK 15E	120 v, 1.5 kw, single phase	
074057	CK 20E	240 V / 208 V, 2.0 kW, single phase	
CKT fan	heater with tin	ner	\$205.00
230345	CKT 15E	120 v, 1.5 kw, single phase	
230346	CKT 20E	240 v / 208 v, 2.0 kW, single phase	







CNS-E convection heater					
231543	CNS 100-2 E	240 v / 208 v, 1.0 kw, single phase	⁵ 174.00		
231544	CNS 150-2 E	240 v / 208 v, 1.5 kw, single phase	°199.00		
231545	CNS 200-2 E	240 v / 208 v, 2.0 kw, single phase	°224.00		
231546	CNS 240-2 E	240 v / 208 v, 2.4 kw, single phase	°249.00		
233586	CNS 100-1 E	120 V, 1.0 kW, single phase	⁵ 174.00		
233587	CNS 150-1 E	120 V, 1.5 kW, single phase	°199.00		



SHORT-WAVE INFRARED ELECTRIC RADIANT HEATERS

SunWarmth™ radiant heater					
234047	CIR 150-1 I	120 V, 1.5 kW, indoor use, supplied with cord with plug	[°] 249.00		
234048	CIR 150-1 0	120 v, 1.5 kw, indoor/outdoor use, supplied with cord with plug	[°] 299.00		
234049	CIR 200-2 0	240 V, 2.0 kW, indoor/outdoor use, Hard wired, supplied with cord	⁵ 339.00		
234050	CIR 400-2 0	240 V, 2.4 kW, indoor/outdoor use Hard wired, supplied with cord	⁶ 619.00		







TOUCHLESS AUTOMATIC HAND DRYERS

Ultra-quiet.

Galaxy™	Alpine white ABS plastic housing		
073009	Galaxy [™] 1	120 v, 1.85 kw, single phase	
073010	Galaxy [™] 2	240 v / 208 v, 2.0 kw, single phase	
Galaxy [™] M	Aluminum alloy housing with alpine white powder coat finish		\$295.00
073724	Galaxy [™] M 1	120 V, 1.85 kW, single phase	
073725	Galaxy™ M 2	240 v / 208 v, 2.0 kw, single phase	
Galaxy [™] M	Aluminum alloy housing with metallic finish		\$315.00







High speed.

Aluminum alloy h	ousing with alpine white powder coat finish	\$299.00
Ultronic [™] 1 W	120 v, 0.985 kw, single phase	
Ultronic [™] 2 W	240 V / 208 V, 1.0 kW, single phase	
Aluminum alloy h	ousing with stainless steel metallic finish	\$459.00
Ultronic [™] 1 S	120 V, 0.985 kW, single phase	
Ultronic [™] 2 S	240 v / 208 v, 1.0 kW, single phase	
	Ultronic [™] 1 W Ultronic [™] 2 W Aluminum alloy h Ultronic [™] 1 S	Ultronic [™] 2 W 240 v / 208 v, 1.0 kW, single phase Aluminum alloy housing with stainless steel metallic finish Ultronic [™] 1 S 120 v, 0.985 kW, single phase



Products can be mixed in one order to get to a lower price bracket, or to get prepaid shipping. A '75.00 crating charge applies to SBB 300 and SBB 400 tanks only. There is no crating charge for the Accelera', SB-E tanks, or the SBB 600 tank. The Accelera', SB-E tanks, and SBB tanks are always FOB West Hatfield.