

Flow Rate vs Temp. Rise

Power Output of Model ¹	Flow Rate Gallons/Min. Gallons/Hr.	Temperature Rise												
		20°F	30°F	40°F	50°F	60°F	70°F	80°F	90°F	100°F	110°F	120°F	130°F	140°F
12 kW	GPM	4.1	2.7	2.1	1.6	1.4	1.2	1.0	0.9	0.8	0.7	0.7	0.6	0.6
	GPH	246	164	123	98	82	70	61	55	49	45	41	38	35
15 kW	GPM	5.1	3.4	2.6	2.1	1.7	1.5	1.3	1.1	1.0	0.9	0.9	0.8	0.7
	GPH	307	205	154	123	102	88	77	68	61	56	51	47	44
18 kW	GPM	6.1	4.1	3.1	2.5	2.1	1.8	1.5	1.4	1.2	1.1	1.0	1.0	0.9
	GPH	369	246	184	147	123	105	92	82	74	67	61	57	53
24 kW	GPM	8.2	5.5	4.1	3.3	2.7	2.3	2.1	1.8	1.6	1.5	1.4	1.3	1.2
	GPH	492	328	246	197	164	140	123	109	98	89	82	76	70
27 kW	GPM	9.2	6.1	4.6	3.7	3.1	2.6	2.3	2.1	1.8	1.7	1.5	1.4	1.3
	GPH	553	369	277	221	184	158	138	123	111	101	92	85	79
36 kW	GPM	12.3	8.2	6.1	4.9	4.1	3.5	3.1	2.7	2.5	2.2	2.1	1.9	1.8
	GPH	737	492	369	295	246	211	184	164	147	134	123	113	105
48 kW	GPM	16.4	10.9	8.2	6.6	5.5	4.7	4.1	3.6	3.3	3.0	2.7	2.5	2.3
	GPH	983	655	492	393	328	281	246	218	197	179	164	151	140
54 kW	GPM	18.4	12.3	9.2	7.4	6.2	5.3	4.6	4.1	3.7	3.4	3.1	2.8	2.6
	GPH	1106	737	553	442	369	316	277	246	221	201	184	170	158
60 kW	GPM	20.5	13.7	10.2	8.2	6.8	5.9	5.1	4.6	4.1	3.7	3.4	3.2	2.9
	GPH	1229	819	614	492	410	351	307	273	246	223	205	189	176
72 kW	GPM	24.6	16.4	12.3	9.8	8.2	7.0	6.1	5.5	4.9	4.5	4.1	3.8	3.5
	GPH	1475	983	737	590	492	421	369	328	295	268	246	227	211
81 kW	GPM	27.7	18.4	13.8	11.0	9.2	7.9	6.9	6.1	5.5	5.0	4.6	4.3	4.0
	GPH	1659	1106	829	664	553	474	415	369	332	302	277	255	237
90 kW	GPM	30.7	20.5	15.4	12.3	10.2	8.8	7.7	6.8	6.1	5.6	5.1	4.7	4.4
	GPH	1843	1229	922	737	614	527	461	410	369	335	307	284	263
108 kW	GPM	36.9 ²	24.6	18.4	14.7	12.3	10.5	9.2	8.2	7.4	6.7	6.1	5.7	5.3
	GPH	2212 ²	1475	1106	885	737	632	553	492	442	402	369	340	316
120 kW	GPM	40.0 ²	27.3	20.5	16.4	13.7	11.7	10.2	9.1	8.2	7.5	6.8	6.3	5.9
	GPH	2400 ²	1638	1229	983	819	702	614	546	492	447	410	378	351
144 kW	GPM	40.0 ²	32.8	24.6	19.7	16.4	14.0	12.3	10.9	9.8	8.9	8.2	7.6	7.0
	GPH	2400 ²	1966	1475	1180	983	843	737	655	590	536	492	454	421

¹ Actual power output varies by model depending on voltage which will affect achievable temp. rise.

² Assumes 1¼" pipe size

ENGINEERING RECOVERY CHART & SPECIFICATIONS

STIEBEL ELTRON

COMMERCIAL INDUSTRIAL 3-PHASE WATER HEATING

	Item Number	Voltage 3-phase	KW	Full Load Amp Draw	3P Breaker Size (A)	No. of Elements	Pipe Size (inches)	Standard Enclosure Size (W x H x D in inches) Excluding fittings
CF 12 KW	CF-012-208D	208	11.27	31.27	35	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CF-012-240D	240	12.50	30.07	35			
	CF-012-400Y	400 Wye	12.41	17.91	20			
	CF-012-480Y	480 Wye	13.50	16.24	20			
CF 15 KW	CF-015-208D	208	15.77	43.78	50	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CF-015-240D	240	15.00	36.08	40			
	CF-015-400Y	400 Wye	13.78	19.88	25			
	CF-015-480Y	480 Wye	16.65	20.03	25			
	CF-015-480D	480	18.00	21.65	25			
CF 18 KW	CF-018-208D	208	18.00	49.96	60	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CF-018-240D	240	18.00	43.30	50			
	CF-018-400Y	400 Wye	19.29	27.84	30			
	CF-018-480Y	480 Wye	18.00	21.65	25			
	CF-018-480D*	480	18.00	21.65	25	6		
CF 24 KW	CF-024-208D	208	22.53	62.55	70	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CF-024-240D	240	25.00	60.14	70			
	CF-024-400D	400	25.00	36.08	40			
	CF-024-400Y	400 Wye	24.82	35.82	40			
	CF-024-480D	480	25.00	30.07	35			
	CF-024-480Y	480 Wye	22.20	26.70	30			
	CF-024-575D	575	24.00	24.10	30			
	CF-027-208D	208	27.04	75.06	80	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
CF 27 KW	CF-027-240D	240	27.02	65.01	80			
	CF-027-400D	400	29.17	42.10	50			
	CF-027-400Y	400 Wye	27.55	39.77	45			
	CF-027-480D	480	27.02	32.51	40			
	CF-027-480Y	480 Wye	27.00	32.48	40			
CF 36 KW	CF-036-208D	208	36.00	99.93	110	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CF-036-240D	240	36.00	86.60	100			
	CF-036-400D	400	33.28	48.04	60			
	CF-036-400Y	400 Wye	33.06	47.72	60			
	CF-036-480D	480	36.00	43.30	50			
	CF-036-575D	575	36.00	36.15	40			
CF 48 KW	CF-048-208D	208	45.07	125.09	150	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CF-048-240D	240	50.00	120.28	150			
	CF-048-400D	400	48.61	70.16	80			
	CF-048-480D	480	50.00	60.14	70			
	CF-048-575D	575	47.99	48.19	60			
CF 54 KW	CF-054-208D	208	54.08	150.11	175	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CF-054-240D	240	54.05	130.02	150			
	CF-054-400D	400	58.33	84.20	100			
	CF-054-480D	480	54.05	65.01	80			
CF 60 KW	CF-060-208D	208	63.09	175.13	200	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CF-060-240D	240	60.00	144.34	175			
	CF-060-400D	400	66.57	96.08	110			
	CF-060-480D	480	60.00	72.17	80			
CF 72 KW	CF-072-208D	208	72.00	199.85	225	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CF-072-240D	240	72.00	173.21	200			
	CF-072-480D	480	72.00	86.60	100			
	CF-072-575D	575	72.00	72.29	80			
CF 81 KW	CF-081-400D	400	75.00	108.25	125	18	1	24 x 48 x 13 ⁵ / ₈
	CF-081-480D	480	81.07	97.52	110			
CF 90 KW	CF-090-400D	400	87.50	126.30	150	18	1	24 x 48 x 13 ⁵ / ₈
	CF-090-480D	480	90.00	108.25	125			
CF 108 KW	CF-108-400D	400	99.85	144.12	175	18	1	24 x 48 x 13 ⁵ / ₈
	CF-108-480D	480	108.00	129.90	150			
	CF-108-575D	575	108.00	108.44	125			
CF 120 KW	CF-120-400D	400	116.67	168.39	200	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CF-120-480D	480	120.00	144.34	175			
CF 144 KW	CF-144-400D	400	133.14	192.17	225	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CF-144-480D	480	144.00	173.21	200			
	CF-144-575D	575	144.00	144.59	175			

Fixed temperature thermostat
MUST BE
specified with order.

Available thermostats (°F)
for all CF models
90, 110, 125, 145, 155, 185

*CF-018 480 V Delta (6-element
heater) available at extra cost

rev. 4-2020 Due to our continuous process of engineering and technological advancement, specifications may change without notice.

ENGINEERING RECOVERY CHART & SPECIFICATIONS

STIEBEL ELTRON

COMMERCIAL INDUSTRIAL 3-PHASE WATER HEATING

	Item Number	Voltage 3-phase	KW	Full Load Amp Draw	3P Breaker Size (A)	No. of Elements	Pipe Size (inches)	Standard Enclosure Size (W x H x D in inches) Excluding fittings
CE 12 KW	CE-012-208D	208	11.27	31.27	35	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CE-012-240D	240	12.50	30.07	35			
	CE-012-400Y	400 Wye	12.41	17.91	20			
	CE-012-480Y	480 Wye	13.50	16.24	20			
CE 15 KW	CE-015-208D	208	15.77	43.78	50	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CE-015-240D	240	15.00	36.08	40			
	CE-015-400Y	400 Wye	13.78	19.88	25			
	CE-015-480Y	480 Wye	16.65	20.03	25			
	CE-015-480D	480	18.00	21.65	25			
CE 18 KW	CE-018-208D	208	18.00	49.96	60	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CE-018-240D	240	18.00	43.30	50			
	CE-018-400Y	400 Wye	19.29	27.84	30			
	CE-018-480Y	480 Wye	18.00	21.65	25			
	CE-018-480D*	480	18.00	21.65	25	6		
CE 24 KW	CE-024-208D	208	22.53	62.55	70	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CE-024-240D	240	25.00	60.14	70			
	CE-024-400D	400	25.00	36.08	40			
	CE-024-400Y	400 Wye	24.82	35.82	40			
	CE-024-480D	480	25.00	30.07	35			
	CE-024-480Y	480 Wye	22.20	26.70	30			
	CE-024-575D	575	24.00	24.10	30			
CE 27 KW	CE-027-208D	208	27.04	75.06	80	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CE-027-240D	240	27.02	65.01	80			
	CE-027-400D	400	29.17	42.10	50			
	CE-027-400Y	400 Wye	27.55	39.77	45			
	CE-027-480D	480	27.02	32.51	40			
	CE-027-480Y	480 Wye	27.00	32.48	40			
CE 36 KW	CE-036-208D	208	36.00	99.93	110	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CE-036-240D	240	36.00	86.60	100			
	CE-036-400D	400	33.28	48.04	60			
	CE-036-400Y	400 Wye	33.06	47.72	60			
	CE-036-480D	480	36.00	43.30	50			
	CE-036-575D	575	36.00	36.15	40			
CE 48 KW	CE-048-208D	208	45.07	125.09	150	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CE-048-240D	240	50.00	120.28	150			
	CE-048-400D	400	48.61	70.16	80			
	CE-048-480D	480	50.00	60.14	70			
	CE-048-575D	575	47.99	48.19	60			
CE 54 KW	CE-054-208D	208	54.08	150.11	175	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CE-054-240D	240	54.05	130.02	150			
	CE-054-400D	400	58.33	84.20	100			
	CE-054-480D	480	54.05	65.01	80			
CE 60 KW	CE-060-208D	208	63.09	175.13	200	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CE-060-240D	240	60.00	144.34	175			
	CE-060-400D	400	66.57	96.08	110			
	CE-060-480D	480	60.00	72.17	80			
CE 72 KW	CE-072-208D	208	72.00	199.85	225	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CE-072-240D	240	72.00	173.21	200			
	CE-072-480D	480	72.00	86.60	100			
	CE-072-575D	575	72.00	72.29	80			
CE 81 KW	CE-081-400D	400	75.00	108.25	125	18	1	24 x 48 x 13 ⁵ / ₈
	CE-081-480D	480	81.07	97.52	110			
CE 90 KW	CE-090-400D	400	87.50	126.30	150	18	1	24 x 48 x 13 ⁵ / ₈
	CE-090-480D	480	90.00	108.25	125			
CE 108 KW	CE-108-400D	400	99.85	144.12	175	18	1	24 x 48 x 13 ⁵ / ₈
	CE-108-480D	480	108.00	129.90	150			
	CE-108-575D	575	108.00	108.44	125			
CE 120 KW	CE-120-400D	400	116.67	168.39	200	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CE-120-480D	480	120.00	144.34	175			
CE 144 KW	CE-144-400D	400	133.14	192.17	225	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CE-144-480D	480	144.00	173.21	200			
	CE-144-575D	575	144.00	144.59	175			

*CE-018 480 V Delta (6-element heater) available at extra cost

rev. 4.2020 Due to our continuous process of engineering and technological advancement, specifications may change without notice.

ENGINEERING RECOVERY CHART & SPECIFICATIONS

STIEBEL ELTRON

COMMERCIAL  INDUSTRIAL 3-PHASE WATER HEATING

	Item Number	Voltage 3-phase	KW	Full Load Amp Draw	3P Breaker Size (A)	No. of Elements	Pipe Size (inches)	Standard Enclosure Size (W x H x D in inches) Excluding fittings
CES 12 KW	CES-012-208D	208	11.27	31.27	35	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CES-012-240D	240	12.50	30.07	35			
	CES-012-400Y	400 Wye	12.41	17.91	20			
	CES-012-480Y	480 Wye	13.50	16.24	20			
CES 15 KW	CES-015-208D	208	15.77	43.78	50	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CES-015-240D	240	15.00	36.08	40			
	CES-015-400Y	400 Wye	13.78	19.88	25			
	CES-015-480Y	480 Wye	16.65	20.03	25			
	CES-015-480D	480	18.00	21.65	25			
CES 18 KW	CES-018-208D	208	18.00	49.96	60	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CES-018-240D	240	18.00	43.30	50			
	CES-018-400Y	400 Wye	19.29	27.84	30			
	CES-018-480Y	480 Wye	18.00	21.65	25			
	CES-018-480D*	480	18.00	21.65	25			
CES 24 KW	CES-024-208D	208	22.53	62.55	70	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CES-024-240D	240	25.00	60.14	70			
	CES-024-400D	400	25.00	36.08	40			
	CES-024-400Y	400 Wye	24.82	35.82	40			
	CES-024-480D	480	25.00	30.07	35			
	CES-024-480Y	480 Wye	22.20	26.70	30			
	CES-024-575D	575	24.00	24.10	30			
CES 27 KW	CES-027-208D	208	27.04	75.06	80	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CES-027-240D	240	27.02	65.01	80			
	CES-027-400D	400	29.17	42.10	50			
	CES-027-400Y	400 Wye	27.55	39.77	45			
	CES-027-480D	480	27.02	32.51	40			
	CES-027-480Y	480 Wye	27.00	32.48	40			
CES 36 KW	CES-036-208D	208	36.00	99.93	110	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CES-036-240D	240	36.00	86.60	100			
	CES-036-400D	400	33.28	48.04	60			
	CES-036-400Y	400 Wye	33.06	47.72	60			
	CES-036-480D	480	36.00	43.30	50			
	CES-036-575D	575	36.00	36.15	40			
CES 48 KW	CES-048-208D	208	45.07	125.09	150	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CES-048-240D	240	50.00	120.28	150			
	CES-048-400D	400	48.61	70.16	80			
	CES-048-480D	480	50.00	60.14	70			
	CES-048-575D	575	47.99	48.19	60			
CES 54 KW	CES-054-208D	208	54.08	150.11	175	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CES-054-240D	240	54.05	130.02	150			
	CES-054-400D	400	58.33	84.20	100			
	CES-054-480D	480	54.05	65.01	80			
CES 60 KW	CES-060-208D	208	63.09	175.13	200	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CES-060-240D	240	60.00	144.34	175			
	CES-060-400D	400	66.57	96.08	110			
	CES-060-480D	480	60.00	72.17	80			
CES 72 KW	CES-072-208D	208	72.00	199.85	225	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CES-072-240D	240	72.00	173.21	200			
	CES-072-480D	480	72.00	86.60	100			
	CES-072-575D	575	72.00	72.29	80			
CES 81 KW	CES-081-400D	400	75.00	108.25	125	18	1	24 x 48 x 13 ⁵ / ₈
	CES-081-480D	480	81.07	97.52	110			
CES 90 KW	CES-090-400D	400	87.50	126.30	150	18	1	24 x 48 x 13 ⁵ / ₈
	CES-090-480D	480	90.00	108.25	125			
CES 108 KW	CES-108-400D	400	99.85	144.12	175	18	1	24 x 48 x 13 ⁵ / ₈
	CES-108-480D	480	108.00	129.90	150			
	CES-108-575D	575	108.00	108.44	125			
CES 120 KW	CES-120-400D	400	116.67	168.39	200	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CES-120-480D	480	120.00	144.34	175			
CES 144 KW	CES-144-400D	400	133.14	192.17	225	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CES-144-480D	480	144.00	173.21	200			
	CES-144-575D	575	144.00	144.59	175			

*CES-018 480 V Delta (6-element heater) available at extra cost

rev. 4-2020 Due to our continuous process of engineering and technological advancement, specifications may change without notice.

ENGINEERING RECOVERY CHART & SPECIFICATIONS

STIEBEL ELTRON

COMMERCIAL INDUSTRIAL 3-PHASE WATER HEATING

	Item Number	Voltage 3-phase	KW	Full Load Amp Draw	3P Breaker Size (A)	No. of Elements	Pipe Size (inches)	Standard Enclosure Size (W x H x D in inches) Excluding fittings
CERO 12 KW	CERO-012-208D	208	10.15	28.17	35	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CERO-012-240D	240	12.50	30.07	35			
	CERO-012-400Y	400 Wye	11.48	16.57	20			
	CERO-012-480Y	480 Wye	11.10	13.35	15			
CERO 15 KW	CERO-015-208D	208	13.52	37.53	45	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CERO-015-240D	240	13.51	32.51	40			
	CERO-015-400Y	400 Wye	12.41	17.91	20			
	CERO-015-480Y	480 Wye	16.65	20.03	25			
CERO 18 KW	CERO-018-208D	208	18.00	49.96	60	3	3/4	16 ¹ / ₁₆ x 15 ¹ / ₈ x 9 ¹ / ₈
	CERO-018-240D	240	18.00	43.30	50			
	CERO-018-400Y	400 Wye	16.53	23.86	30			
	CERO-018-480Y	480 Wye	18.00	21.65	25			
	CERO-018-480D*	480	16.66	20.04	25	6		
CERO 24 KW	CERO-024-208D	208	20.30	56.34	70	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CERO-024-240D	240	25.00	60.14	70			
	CERO-024-400D	400	25.00	36.08	40			
	CERO-024-400Y	400 Wye	24.82	35.82	40			
	CERO-024-480D	480	25.00	30.07	35			
	CERO-024-480Y	480 Wye	22.20	26.70	30			
	CERO-024-575D	575	24.00	24.09	30			
CERO 27 KW	CERO-027-208D	208	27.04	75.06	80	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CERO-027-240D	240	27.02	65.01	80			
	CERO-027-480D	480	27.02	32.50	40			
CERO 36 KW	CERO-036-240D	240	36.00	86.60	100	6	3/4	18 ⁵ / ₈ x 21 ⁷ / ₈ x 9 ¹ / ₄
	CERO-036-400D	400	33.28	48.04	60			
	CERO-036-400Y	400 Wye	33.06	47.72	60			
	CERO-036-480D	480	36.00	43.30	50			
	CERO-036-575D	575	36.00	36.15	40			
CERO 48 KW	CERO-048-240D	240	50.00	120.28	150	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CERO-048-400D	400	50.00	72.17	80			
	CERO-048-480D	480	50.00	60.14	70			
	CERO-048-575D	575	47.99	48.19	60			
CERO 54 KW	CERO-054-208D	208	54.08	150.11	175	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CERO-054-240D	240	54.05	130.02	150			
	CERO-054-480D	480	54.05	65.01	70			
CERO 72 KW	CERO-072-240D	240	72.00	173.21	200	12	1	18 ⁵ / ₈ x 30 ¹ / ₂ x 9 ¹ / ₄
	CERO-072-480D	480	72.00	86.60	100			
	CERO-072-575D	575	71.99	72.28	80			
CERO 81 KW	CERO-081-400D	400	75.00	108.25	125	18	1	24 x 48 x 13 ⁵ / ₈
	CERO-081-480D	480	81.07	97.52	110			
CERO 90 KW	CERO-090-480D	480	99.91	120.17	150	18	1	24 x 48 x 13 ⁵ / ₈
CERO 108 KW	CERO-108-400D	400	99.85	144.12	175	18	1	24 x 48 x 13 ⁵ / ₈
	CERO-108-480D	480	108.00	129.90	150			
	CERO-108-575D	575	108.00	108.44	125			
CERO 144 KW	CERO-144-400D	400	133.14	192.17	225	24	1 ¹ / ₄	24 x 48 x 13 ⁵ / ₈
	CERO-144-480D	480	144.00	173.21	200			
	CERO-144-575D	575	144.00	144.59	175			

*CERO-018 480 V Delta (6-element heater) available at extra cost

rev. 4.2020 Due to our continuous process of engineering and technological advancement, specifications may change without notice.