

## DHX Select

### Technical specifications

Model	DHX 10 Select		DHX 15 Select	
Item no.	208580		204812	
Phase - 50/60 Hz	1			
Voltage	240 V	208 V	240 V	208 V
Wattage	9.6 kW	7.2 kW	14.4 kW	10.8 kW
Amperage	40 A	34.6 A	60 A	52 A
Min. recommended circuit breaker size <sup>1</sup>	40 A	35 A	60 A	60 A
Min. recommended wire size <sup>2</sup>	8/2 AWG		6/2 AWG	
Minimum water flow to activate unit	0.264 gpm (1.0 l/min)			
Weight	5.5 lb (2.5 kg)			
Dimensions	Height 14 <sup>1</sup> / <sub>8</sub> " (360 mm) x Width 8" (202 mm) x Depth 4 <sup>5</sup> / <sub>16</sub> " (109 mm)			
Nominal water volume	0.07 gal (0.277 l)			
Max. permissible inlet temperature	149°F (65°C)			
Maximum permissible pressure	145 psi (10 bar)			
Water connections	½" NPT			

<sup>1</sup> Overcurrent protection sized at 100% of load. Tankless water heaters are considered a non-continuous load. Use only GFCI Class A circuit breakers.

<sup>2</sup> Copper conductors with a temperature rating of 75°C or greater must be used. Conductors should be sized to maintain a voltage drop of less than 3% under load.

These are our recommendations. Check local codes for compliance if necessary.



Conforms to UL Std. 499  
Certified to CAN/CSA Std. C22.2 No. 64



Tested and certified by WQA  
against NSF/ANSI/CAN 372  
for lead free compliance.

