

TECHNICAL SERVICE BULLETIN

Complete Cross Reference Guide for Mini™, Mini™-E, DHC, DHC-E, Tempra® & SHC
 Stiebel Eltron has a complete line of tankless electric and mini-tank models for point-of-use to whole house from 1.8 to 36 kW. This guide shows models from other manufacturers and their match to Stiebel Eltron.

American Hometec					STIEBEL ELTRON			
Model	Setting	KW	Voltage	Amps	Model	KW	Voltage	Amp
AHQ-B03X	2	2.4	120	20	Mini 2.5-1	2.4	120	20
	1	3.4	120	28.5	Mini 3.5-1	3.5	120	29
AHQ-C10	3	3.8	208	18.5	DHC 5-2	3.6	208	18
	3	4.8	240	20	DHC 5-2	4.8	240	20
	2	5.7	208	27.5	DHC 8-2	5.4	208	26
	2	7.2	240	30	DHC 8-2	7.2	240	30
	1	7.6	208	36.5	DHC 10-2	7.2	208	35
	1	9.4	240	39.6	DHC 10-2	9.6	240	40
ACQ-TC10Y	3	5.5	277	19.9	DHC 4-3	4.5	277	17
	2	8.3	277	30	DHC 9-3	9.0	277	32.5
	1	9.5	277	34.3	DHC 9-3	9.0	277	32.5
AHQ-T16		13.2	208	64	Tempra 20	14.4	208	70
		16.0	240	68	Tempra 15	14.4	240	60
AHQ-TB32	2	19.0	208	95	Tempra 24	18.0	208	88
	2	25.0	240	104	Tempra 24	24.0	240	100
	1	24.0	208	120	Tempra 29	21.6	208	105
	1	31.0	240	131	Tempra 29	28.8	240	120

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Bosch				STIEBEL ELTRON			
Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
US 3	3.4	120	30	Mini 3.5-1	3.5	120	29
US 6	6.0	277	25				
US 7	7.2	240	30	DHC 8-2	7.2	240	30
US 9	9.5	240	40	DHC 10-2	9.6	240	40
US 12	12.0	240	50	DHC-E 12	12.0	240	50
				Tempra 12	12.0	240	50
WH 17	17.25	240	80	Tempra 20	19.2	240	80
WH 27	26.85	240	120	Tempra 29	28.8	240	120
WH 36	36.0	240	180	Tempra 36	36.0	240	150
ES 2.5 Ariston GL2.5	1.4	120	12	SHC 2.5	1.3	120	11.3
	1.4	120	12	SHC 2.5	1.3	120	11.3
ES 4 Ariston GL4	1.4	120	12	SHC 4	1.3	120	11.3
	1.4	120	12	SHC 4	1.3	120	11.3
ES 8 Ariston GL6+	1.4	120	12	SHC 6	1.3	120	11.3
	1.4	120	12	SHC 6	1.3	120	11.3

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Bradley		STIEBEL ELTRON	
Model			
Keltec	Commercial/Industrial 3-phase	Contact our Tankless Inc. division at 800.826.5537	

Chronomite

STIEBEL ELTRON

Model	KW	Voltage	Amps	Model	KW	Voltage	Amps
SR-15L	1.8	120	15	Mini 2-1	1.8	120	15
	4.1	277	15	DHC 4-3	4.5	277	17
SR-20L	2.4	120	20	Mini 2.5-1	2.4	120	20
	4.2	208	20	Mini 6-2	4.3	208	20.6
	4.8	240	20	DHC 5-2	4.8	240	20
	5.5	277	20	DHC 4-3	4.5	277	17
SR-30L	3.6	120	30	Mini 3.5-1	3.5	120	29
SR-30	6.2	208	30	DHC 8-2	5.4	208	26
	7.2	240	30	DHC 8-2	7.2	240	30
	8.3	277	30	DHC 9-3	9.0	277	32.5
SR-40	8.3	208	40	DHC 10-2	7.2	208	35
	9.6	240	40	DHC 10-2	9.6	240	40
M-15L	4.1	277	15	DHC 4-3	4.5	277	17
M-20L	2.4	120	20	Mini-E 2.5-1	2.4	120	20
	4.2	208	20	Mini-E 6-2	4.3	208	20.6
	4.8	240	20	Mini-E 4-2	3.5	240	14.6
				Mini-E 6-2	5.7	240	23.8
	5.5	277	20	DHC 4-3	4.5	277	17
M-30L	3.6	120	30	Mini-E 3.5-1	3.5	120	29
M-30	6.2	208	30	DHC-E 8/10	5.4	208	26
	7.2	240	30	DHC-E 8/10	7.2	240	30
	8.3	277	30	DHC 9-3	9.0	277	32.5
M-40	8.3	208	40	DHC-E 8/10	7.2	208	35
	9.6	240	40	DHC-E 8/10	9.6	240	40
	11.1	277	40				
M-50	11.5	240	50	DHC-E 12	12.0	240	50
E-46L	4.6	208	22	Mini-E 6-2	4.3	208	20.6
	4.6	240	21	Mini-E 4-2	3.5	240	14.6
				Mini-E 6-2	5.7	240	23.8
E-60L	6.0	208	29	DHC-E 8/10	5.4	208	26
	6.0	240	27	Mini-E 6-2	5.7	240	23.8
E-70L	7.0	208	34	DHC-E 8/10	7.2	208	35
	7.0	240	31	DHC-E 8/10	7.2	240	30
E-80L	8.0	208	38	DHC-E 8/10	7.2	208	35
	8.0	240	36	DHC-E 8/10	7.2	240	30
E-90L	9.0	240	40	DHC-E 8/10	9.6	240	40
E-46S	4.6	208	22	Mini-E 6-2	4.3	208	20.6
	4.6	240	21	Mini-E 6-2	5.7	240	23.8
E-60S	6.0	208	29	DHC-E 8/10	5.4	208	26
	6.0	240	27	Mini-E 6-2	5.7	240	23.8
E-70S	7.0	208	34	DHC-E 8/10	7.2	208	35
	7.0	240	31	DHC-E 8-10	7.2	240	30
E-80S	8.0	208	38	DHC-E 8/10	7.2	208	35
	8.0	240	36	DHC-E 8/10	7.2	240	30
E-90S	9.0	240	40	DHC-E 8/10	9.6	240	40
CMT 1.3	1.4	120	12				
CMT 2.5	1.4	120	12	SHC 2.5	1.3	120	11.3
CMT 4	1.4	120	12	SHC 4	1.3	120	11.3
ER_3P	18-72	208 240 480		Contact our Tankless Inc. division at 800.826.5537			

CHRONOMITE SUFFIX
L = Low flow rate 0.5 gpm
S = Standard flow rate 1 gpm

CHRONOMITE PREFIX
M = Factory preset available @ 104/110/120°
E = Thermostatic

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

EcoSmart

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
POU 3.5	3.5	120	29	Mini 3.5-1	3.5	120	29
POU 6	6.0	240	25	DHC 6-2	6.0	240	25
ECO 8	8.0	240	33	DHC-E 8/10	7.2	240	30
ECO 11	13.6	240	57	DHC-E 12	12.0	240	50
				Tempra 12	12.0	240	50
				Tempra 15	14.4	240	60
ECO 18	18.0	240	75	Tempra 20	19.2	240	80
ECO 24	24.0	240	100	Tempra 24	24.0	240	100
ECO 27	27.0	240	112.5	Tempra 29	28.8	240	120
ECO 36	36.0	240	150	Tempra 36	36.0	240	150
ECO Mini 2.5	1.4	120	12	SHC 2.5	1.3	120	11.3
ECO Mini 4	1.4	120	12	SHC 4	1.3	120	11.3
ECO Mini 6	1.4	120	12	SHC 6	1.3	120	11.3

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

Eemax

Home Advantage Series

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
HA008240	8.0	240	33	DHC-E 8/10	7.2	240	30
HA011240	11.0	240	46	DHC-E 12	12.0	240	50
				Tempra 12	12.0	240	50
HA013240	13.0	240	54	Tempra 15	14.4	240	60 (2x30)
HA018240	18.0	240	75	Tempra 20	19.2	240	80 (2x40)
HA024240	24.0	240	100	Tempra 24	24.0	240	100 (2x50)
HA027240	27.0	240	112	Tempra 29	28.8	240	120 (3x40)
HA036240	36.0	240	152	Tempra 36	36.0	240	150 (3x50)

Series Two - Twin Heating Module

EX120	11.5	240	48	Tempra 12	12.0	240	50
EX144	15.0	240	64 (2x32)	Tempra 15	14.4	240	60 (2x30)
EX190	19.0	240	80 (2x40)	Tempra 20	19.2	240	80 (2x40)
EX023240	23.0	240	96 (2x48)	Tempra 24	24.0	240	100 (2x50)
EX1608	16.6	208	80 (2x40)	Tempra 20	14.4	208	70 (2x35)
EX160	16.0	277	58 (2x29)				
EX200	20.0	277	72 (2x36)				

Series Three - Three Heating Modules

EX280	28.0	240	120 (3x40)	Tempra 29	28.8	240	120 (3x40)
-------	------	-----	------------	-----------	------	-----	------------

Series Four - Four Heating Modules

EX380	38.0	240	160 (4x40)	Tempra 36	36.0	240	150 (3x50)
-------	------	-----	------------	-----------	------	-----	------------

Series Six - Six Heating Modules

EX360	36.0	480/277	43	<p>These models were replaced by the Eemax AP SpecAdvantage line.</p> <p>Contact our Tankless Inc. division at 800.826.5537 for 3-phase crossover recommendations for SpecAdvantage and SafeAdvantage.</p>
EX480	48.0	480/277	58	
EX540	54.0	480/277	65	
EX630	63.0	480/277	76.0	
EX360	36.0	208/120	100	
EX480	48.0	208/120	133	

Mini Tank

EMT1	1.4	120	12				
EMT2.5	1.4	120	12	SHC 2.5	1.3	120	11.3
EMT4	1.4	120	12	SHC 4	1.3	120	11.3
EMT6	1.4	120	12	SHC 6	1.3	120	11.3

EEMAX SPECIFICATION OPTIONS
 TC - Hot or cold feed-staged
 FS - Factory set ambient 180°
 ML - Multi lavs
 T2 - Hot or cold feed-parallel
 S - Sanitation 180*

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Eemax

STIEBEL ELTRON

“Single Point”

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
SP2412	2.4	120	20	Mini 2.5-1	2.4	120	20
SP3012	3.0	120	25	DHC 3-1	3.0	120	25
				Mini 3-1	3.0	120	25
SP3512	3.5	120	29	Mini 3.5-1	3.5	120	29
SP3208	3.0	208	14.4	DHC 4-2	2.9	208	14
				Mini 4-2	2.6	208	12.7
SP4208	4.1	208	19.7	DHC 6-2	4.5	208	22
				Mini 6-2	4.3	208	20.6
SP35	3.5	240	14.6	DHC 3-2	3.3	240	14
				Mini 4-2	3.5	240	15.2
SP48	4.8	240	20	DHC 5-2	4.8	240	20
SP55	5.5	240	29.9	DHC 6-2	6.0	240	25
				Mini 6-2	5.7	240	23.8
SP3277	3.0	277	10.8				
SP4277	4.1	277	14.8	DHC 4-3	4.5	277	17

“Flow Control”

EX8208	8.3	208	8.3	DHC 10-2	7.2	208	35
EX35	3.5	240	15	DHC 3-2	3.3	240	14
				Mini 4-2	3.5	240	14.6
EX 48	4.8	240	20	DHC 5-2	4.8	240	20
EX55	5.5	240	23	DHC 6-2	6.0	240	25
				Mini 6-2	5.7	240	23.8
EX65	6.5	240	27	DHC 6-2	6.0	240	25
EX75	7.5	240	32	DHC 8-2	7.2	240	30
EX95	9.5	240	40	DHC 10-2	9.6	240	40
EX60	6.0	277	22				
EX80	8.0	277	29	DHC 9-3	9.0	277	32.5
EX90	9.0	277	33	DHC 9-3	9.0	277	32.5
EX100	10.0	277	36	DHC 9-3	9.0	277	32.5

“Thermostatic” Single Element

EX2412T	2.4	120	20	Mini-E 2.5-1	2.4	120	21
EX3012T	3.0	120	25	Mini-E 3-1	3.0	120	25
EX3512T	3.5	120	29	Mini-E 3.5-1	3.5	120	30
EX35T	3.5	240	15	Mini-E 4-2	3.5	240	14.6
EX48T	4.8	240	20	Mini-E 6-2	5.7	240	23.8
EX55T	5.5	240	23	Mini-E 6-2	5.7	240	23.8
EX65T	6.5	240	27	Mini-E 6-2	5.7	240	23.8
EX75T	7.5	240	32	DHC-E 8/10	7.2	240	30
EX95T	9.5	240	40	DHC-E 8/10	9.6	240	40
EX012240T	11.5	240	48	DHC-E 12	12.0	240	50
EX8208T	8.3	208	40	DHC-E 8/10	7.2	208	35
EX3277T	3	277	10.8				
EX4277T	4.1	277	14.8				
EX60T	6.0	277	22				
EX80T	8.0	277	29				
EX90T	9.0	277	33				
EX100T	10.0	277	36				

EEMAX SPECIFICATION OPTIONS
 TC - Hot or cold feed-staged
 FS - Factory set ambient 180°
 ML - Multi lavs
 T2 - Hot or cold feed-parallel
 S - Sanitation 180*

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a “Trend” model and a “Plus” model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water “surprise” with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Hubbell

STIEBEL ELTRON

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
R003-2S	3.0 2.25	240 208	12.5 10.8	DHC 3-2 DHC 3-2	3.3 2.5	240 208	14 12
R005-2S	4.5 3.37	240 208	19 16.2	DHC 5-2 DHC 5-2	4.8 3.6	240 208	20 18
R007-2S	7.0 5.2	240 208	29 25	DHC 8-2 DHC 8-2	7.2 5.4	240 208	30 26
R009-2S	9.0 6.7	240 208	37.5 32.2	DHC 10-2 DHC 10-2	9.6 7.2	240 208	40 35
R011-2S	11.0 8.2	240 208	46 39.4	Tempra 12 Tempra 12	12.0 9.0	240 208	50 44
R014-2S	14.0 10.5	240 208	58 50.4	Tempra 15 Tempra 15	14.4 10.8	240 208	60 52
R016-2S	16.0 12.0	240 208	67 57.6	Tempra 15 Tempra 15	14.4 10.8	240 208	60 52
R018-2S	18.0 13.5	240 208	75 64.9	Tempra 20 Tempra 20	19.2 14.4	240 208	80 70
R021-2S	21.0 15.7	240 208	87.5 75.7	Tempra 20 Tempra 20	19.2 14.4	240 208	80 70
R024-2S	24.0 18.0	240 208	100 86.5	Tempra 24 Tempra 24	24.0 18.0	240 208	100 88
R027-2S	27.0 20.25	240 208	112 97.3	Tempra 29 Tempra 29	28.8 21.6	240 208	120 105
HX / TX	thru 54	600 208		Contact our Tankless Inc. division at 800.826.5537			

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

iHeat

STIEBEL ELTRON

Hot Spot A-Series

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
A-10	4.8	120	40	Mini 3.5-1	3.5	120	29
A-35	3.5	120	29	Mini 3.5-1	3.5	120	29
A-67	6.0	240	25	Mini 6-2 DHC 6-2	5.7 6.0	240 240	23.8 25

ADK M Series

M-4	3.5	120	30	Mini-E 3.5-1	3.5	120	29
M-7	6.7	220	30	DHC-E 8/10	7.2	240	30
M-9	8.9	220	41	DHC-E 8/10	9.6	240	40
M-12	12.4	220	56	DHC-E 12 Tempra 12	12.0 12.0	240 240	50 50
M-14	13.0	220	59	Tempra 15	14.4	240	60
M-16	16.0	240	66	Tempra 15	14.4	240	60

AH Pro Performer

AHS-11D	11.0	240	46	DHC-E 12 Tempra 12	12.0 12.0	240 240	50 50
AHS-14D	14.0	240	58	Tempra 15	14.4	240	60
AHS-16D	16.0	240	66	Tempra 15	14.4	240	60
AHS-18D	18.0	240	75	Tempra 20	19.2	240	80
AHS-21D	21.0	240	87.5	Tempra 20	19.2	240	80
AHS-24D	24.0	240	100	Tempra 24	24.0	240	100
AHS-27D	27.0	240	112.5	Tempra 29	28.8	240	120

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Powerstream / Powerstar

STIEBEL ELTRON

Powerstream

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
RP3	3.0	120	29	DHC 3-1	3.0	120	25
				Mini 3-1	3.0	120	25
RP1	7.1	208	35	DHC 10-2	7.2	208	35
RP1	3.5	208	18	DHC 5-2	3.6	208	18
RP1	9.5	240	40	DHC 10-2	9.6	240	40
RP1	4.75	240	20	DHC 5-2	4.8	240	20
RP2	6.0	277	22	DHC 4-3	4.5	277	17
RP2	3.0	277	11	DHC 4-3	4.5	277	17
RP7	7.0	240	30	DHC 8-2	7.2	240	30
RP7	3.5	240	15	DHC 4-2	3.8	240	16
				Mini 4-2	3.5	240	14.6
RP9	9.5	277	35	DHC 9-3	9.0	277	32.5
RP9	4.8	277	18	DHC 4-3	4.5	277	17
“Thermostatic Model”							
RP12T	12.0	240	50	Tempra 12	12.0	240	50
				DHC-E 12	12.0	240	50

Powerstar

AE 3.4	3.4	120	29	DHC 3-1	3.0	120	25
				Mini 3.5-1	3.5	120	29
AE 7.2	7.0	240	30	DHC 8-2	7.2	240	30
AE 9.5	7.1	208	35	DHC 10-2	7.2	208	35
AE 9.5	9.5	240	40	DHC 10-2	9.6	240	40
AE 12	12.0	240	50	DHC-E 12	12.0	240	50
				Tempra 12	12.0	240	50

Two Element

AE115	13.00	208	69 (2x40)	Tempra 20	14.4	208	70 (2x35)
AE115	17.25	240	80 (2x40)	Tempra 20	19.2	240	80 (2x40)

Three Element

AE125	20.00	208	101 (3x40)	Tempra 29	21.6	208	105 (3x35)
AE125	26.85	240	120 (3x50)	Tempra 29	28.8	240	120 (3x40)

Rheem

STIEBEL ELTRON

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
RTEX-04	3.5	120	29	Mini-E 3.5-1	3.5	120	29
RTEX-06	5.5	220	29	Mini-E 6-2	5.7	240	23.8
RTEX-08	8.0	240	33	DHC-E 8/10	7.2	240	30
RTEX-11	11.0	240	46	DHC-E 12	12.0	240	50
RTEX-13	13.0	240	54	Tempra 12	12.0	240	50
				Tempra 15	14.4	240	60
RTEX-18	18.0	240	75	Tempra 20	19.2	240	80
RTEX-24	24.0	240	100	Tempra 24	24	240	100
RTEX-27	27.0	240	112	Tempra 29	28.8	240	120
RTEX-36	36.0	240	150	Tempra 36	36	240	150

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a “Trend” model and a “Plus” model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water “surprise” with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Seisco

STIEBEL ELTRON

Point of Use

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
POU24-120	2.4	120	20	Mini 2.5-1	2.4	120	20
				Mini-E 2.5-1*	2.4	120	20
POU30-120	3.0	120	25	Mini 3-1	3.0	120	25
				Mini-E 3-1*	3.0	120	25
				DHC 3-1	3.0	120	25
POU35-120	3.5	120	29.2	Mini 3.5-1	3.5	120	29
				Mini-E 3.5-1*	3.5	120	29
POU35-240	3.5	240	14.6	Mini 4-2	3.5	240	14.6
				Mini-E 4-2*	3.5	240	14.6
	2.6	208	12.6	Mini 4-2	2.6	208	12.7
				Mini-E 4-2*	2.6	208	12.7
POU45-240	4.5	240	18.8	DHC 5-2	4.8	240	20
	3.4	208	16.2	DHC 5-2	3.6	208	18
POU55-240	5.5	240	22.9	Mini 6-2	5.7	240	23.8
				Mini-E 6-2*	5.7	240	23.8
	4.1	208	19.8	Mini 6-2	4.3	208	20.6
				Mini-E 6-2*	4.3	208	20.6
POU70-240	7.0	240	29.2	DHC 8-2	7.2	240	30
				DHC-E 8/10*	7.2	240	30
	5.3	208	25.2	DHC 8-2	5.4	208	26
				DHC-E 8/10*	5.4	208	26
POU80-240	8.0	240	33.3	DHC 8-2	7.2	240	30
				DHC-E 8/10*	7.2	240	30
	6.0	208	28.8	DHC 8-2	5.4	208	26
				DHC-E 8/10*	5.4	208	26
POU90-240	9.0	240	37.5	DHC 10-2	9.6	240	40
				DHC-E 8/10*	9.6	240	40
	6.8	208	32.5	DHC 10-2	7.2	208	35
				DHC-E 8/10*	7.2	208	35
POU78-208	7.8	208	37.5	DHC 10-2	7.2	208	35
				DHC-E 8/10*	7.2	208	35
POU120-240	12.0	240	50	DHC-E 12* DHC-E	12.0	240	50
	9.0	208	43.3	12*	9.0	208	44
POU140-240	14.0	240	58.3	Tempra 15*	14.4	240	60
	10.5	208	50.5	Tempra 15*	10.8	208	52
POU30-277	3.0	277	10.8				
POU40-277	4.0	277	14.4	DHC 4-3	4.5	277	17
POU60-277	6.0	277	21.7				
POU73-277	7.0	277	25.3				
POU90-277	9.0	277	32.5	DHC 9-3	9.0	277	32.5
POU120-277	12.0	277	43.3				
POU140-277	14.0	277	50.5				
Single Chamber							
RA-14-240	14.0	240	58.3	Tempra 15*	14.4	240	60
	10.5	208	50.5	Tempra 15*	10.8	208	52
RA-16-240	16.0	240	66.7	Tempra 15*	14.4	240	60
	12.0	208	57.7	Tempra 15*	10.8	208	52

*Thermostatic unit

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.

Seisco

STIEBEL ELTRON

Two Chamber

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
RA-14-2	14.0 10.5	240 208	58.3 50.5	Tempra 15 ⁺ Tempra 15 ⁺	14.4 10.8	240 208	60 52
RA-16-2	16.0 12.0	240 208	66.7 57.7	Tempra 15 ⁺ Tempra 15 ⁺	14.4 10.8	240 208	60 52
RA-18-240	18.0 13.5	240 208	75.0 64.9	Tempra 20 ⁺ Tempra 20 ⁺	19.2 14.4	240 208	80 70
RA-22-240	22.0 16.5	240 208	91.7 79.3	Tempra 20 ⁺ Tempra 24 ⁺	19.2 18.0	240 208	80 88
RA-24-240	24.0 18.0	240 208	100.0 86.5	Tempra 24 ⁺ Tempra 24 ⁺	24.0 18.0	240 208	100 88
RA-28-240	28.0 21.0	240 208	116.7 101.0	Tempra 29 ⁺ Tempra 29 ⁺	28.8 21.6	240 208	120 105

Four Chamber

RA-18-4	18.0 13.5	240 208	75.0 64.9	Tempra 20 ⁺ Tempra 20 ⁺	19.2 14.4	240 208	80 70
RA-22-4	22.0 16.5	240 208	91.7 79.3	Tempra 20 ⁺ Tempra 20 ⁺	19.2 14.4	240 208	80 70
RA-28-4	28.0 21.0	240 208	116.7 101.0	Tempra 29 ⁺ Tempra 29 ⁺	28.8 21.6	240 208	120 105
RA-32-240	32.0 24.0	240 208	133.3 115.4	Tempra 36 ⁺ Tempra 36 ⁺	36.0 27.0	240 208	150 132
RA-28-208	28.0	208	134.6	Tempra 36 ⁺	27.0	208	132

Mini-Tank

SMT2.5	1.1	120	12.0	SHC 2.5	1.3	120	11.3
SMT4	1.4	120	12.0	SHC 4	1.3	120	11.3
SMT6	1.4	120	12.0	SHC 6	1.3	120	11.3

*Thermostatic unit

A Mini can be installed above or below a fixture and with outlet pipes facing up or down.

IF YOU ARE REPLACING ANY EXISTING INSTALLATION WITH A DIFFERENT APPLIANCE, MAKE SURE THE NEW ELECTRICAL REQUIREMENTS WILL BE MET.

Titan

STIEBEL ELTRON

Model	KW	Voltage	Amps	Model	KW	Voltage	Amp
N-10	3.2	120	29	Mini-E 3-1	3.0	120	25
N-42	4.2	240	19	Mini-E 4-2	3.5	240	14.6
N-64	6.4	240	29	Mini-E 6-2	5.7	240	23.8
N-75	7.5	240	34	DHC-E 8/10	7.2	240	30
N-85	8.5	240	38	DHC-E 8/10	9.6	240	40
N-100	10.8	240	49	DHC-E 8/10	9.6	240	40
N-120	11.8	240	54	DHC-E 12 Tempra 12	12.0 12.0	240 240	50 50
N-160	16.0	240	66	Tempra 15	14.4	240	60
N-180	18.0	240	75	Tempra 20	19.2	240	80
N-210	21.0	240	88	Tempra 20	19.2	240	80
N-270	27.0	240	113	Tempra 29	28.8	240	120

Each Stiebel Eltron Tempra® is available as a "Trend" model and a "Plus" model.

Tempra® Plus models have Advanced Flow Control™, patented in Germany by Stiebel Eltron, to automatically maintain set temperature by tempering flow rate if hot water demand temporarily exceeds capacity. Stiebel Eltron is the only tankless electric manufacturer to offer Advanced Flow Control™. There's never a cold water "surprise" with Tempra® Plus.

Self-Modulating Energy Technology in both Tempra® Trend & Tempra® Plus saves money by continually ensuring the least amount of energy is used to heat the water.